



HammerHead™ 12 Switch Accessory Control

Product Summary

- Field configurable, Windows® compatible, programmable 12 switch accessory control panel;
- Select from 7 switch types configured with any laptop PC;
- Switches can be re-programmed and labels re-printed on site;
- Configuration software included with system;

Product Application

- All types and sizes of truck chassis for mobile electronic and many hydraulic functions;
- All-in-one accessory systems panel;

Programmable Switch Functions

- Momentary On/Off: Hold on, release off;
- On/Off: Press on, press off;
- Delayed On: Hold on (delays for programmed time) before actuation, press again to turn off;
- Delayed Off: Press to turn on, for a programmed time (auto shut off);
- Default On: On at start up, press for off;
- Default On/Off: Initial state is "on" when power is applied; on/off thereafter;

Switch Cominations

- Mutually exclusive switches - one switch turns off up to 4 others;
- Combination switches - one switch acts as master for up to 4 other switches;
- Two button guard - requires that two switches be pushed to actuate function;
- Sequencing - Series of switches linked in functional sequence; canceling the first switch automatically initiates the next switch in the sequence;

Relay Protection and Breakers

- Each switch controls a relay and is protected by a 10amp auto reset breaker;

Switch Configuration Utility

- **HammerConfig.exe** utility works on any Windows 2000 (or newer) computer;

Electronic Backpack

- **HammerHead™** System communicating on Cirus Bus;

System Mounting

- Seat-mounted or pedestal mounted Flip-Arm console;
- Seat-mounted or pedestal mounted Mini Angle Deck console;
- Stand Alone, bracket mount;

Operating Temperature Range

- Minimum: -20 degrees Centigrade; Maximum: 70 degrees Centigrade

Power Requirements

- Minimum: 11 Volts DC; Maximum: 15 Volts DC
- Maximum: 15 A; Fuses rated at 10A