



# Liquid Control™ Spreader Control

<b>Product Summary</b>	<ul style="list-style-type: none"> <li>• Ground speed oriented, open or closed loop, single channel proportional liquid control, including data logging for storm and season totals;</li> <li>• Precision application using up to 6 pre-defined rates;</li> <li>• "Single tier" or "integrated dual tier" spray boom control;</li> </ul>
<b>Product Application</b>	<ul style="list-style-type: none"> <li>• Anti-Icing De-Icing trucks;</li> <li>• Precise tracking of application performed;</li> </ul>
<b>Open or Closed Loop Spreading Channel</b>	<ul style="list-style-type: none"> <li>• Anti-Ice system controlling applications up to three booms and two tiers (ground speed oriented);</li> </ul>
<b>Spreading Rate Definitions</b>	<ul style="list-style-type: none"> <li>• Up to 6 application rates definition for Anti-Ice;</li> </ul>
<b>Data Logging by Material Name for Billing Purposes</b>	<ul style="list-style-type: none"> <li>• Select specific application rate definitions and related data logging for use on specific roads (State vs. County, vs. City roads);</li> </ul>
<b>Storm and Season Totals</b>	<ul style="list-style-type: none"> <li>• System logs application amounts for the storm and the season. (Storm total is operator re-settable);</li> </ul>
<b>Blast and Pass</b>	<ul style="list-style-type: none"> <li>• Blast is programmable (on/off, momentary or timed);</li> <li>• Remote Blast and Remote Pass accessible using Cirrus plow controls;</li> </ul>
<b>Output Signal</b>	<ul style="list-style-type: none"> <li>• Multiple Frequency settings for ease of valve compatibility;</li> </ul>
<b>Power Safety</b>	<ul style="list-style-type: none"> <li>• <b>Power Safe™</b> signals prevents random grounds powering any hydraulics system attached (auger, spinner, conveyor, etc);</li> </ul>
<b>Display Type</b>	<ul style="list-style-type: none"> <li>• 4 character lines 20 characters per line on the Graphic LCD;</li> </ul>
<b>System Mounting</b>	<ul style="list-style-type: none"> <li>• Seat-mounted or pedestal mounted Flip-Arm console;</li> <li>• Seat mounted or pedestal mounted Mini-Angle Deck console;</li> <li>• Stand Alone;</li> </ul>
<b>Warning Indicators</b>	<ul style="list-style-type: none"> <li>• Integrated visible (LCD) and audible (buzzer) for spreading alarms;</li> </ul>
<b>Operating Temperature Range</b>	<ul style="list-style-type: none"> <li>• Minimum: -20 degrees Centigrade; Maximum: 70 degrees Centigrade;</li> </ul>
<b>Power Requirements</b>	<ul style="list-style-type: none"> <li>• Minimum: 11 Volts DC; Maximum: 15 Volts DC</li> <li>• Maximum: 10 A; Fuses rated at 10 A</li> </ul>

© 2005 Cirrus Controls, LLC